

UNLOADERS, VALVES & STRAINERS



UNLOADERS

- UU110 Unloader For PH326 (AR)
- UU150 Unloader 3.5@3000 Hypro
- UU154 Unloader / Regulator 2300 psi (2SF)
- UU176 Unloader 3000 @ 7 (4SF)
- UU260 Unloader 3600 ST26I (No switch)
- UU261 Unloader 3600 w/ Pressure Switch
- UU262 Switch, ST260 Unloader
- UU300 Regulator 2000 psi @ 32 gpm
- UU320 Unloader / Regulator 4000 @ 21
- UU323 Unloader 4200 psi 8 gpm
- UU325 Unloader 5800 psi @ 21
- UU370 Unloader 2-4 @ 3000 K7-0
- UU371 Unloader 3-5 @ 3000 K7-1
- UU372 Unloader 5-7 @ 3000 K7-2
- UU373 Unloader 8-11 @ 3000 K7-3
- UU377 Bypass Orifice K-7 #0
- UU379 Bypass Fitting K7 #1
- UU380 Unloader w/ Switch 3500 @ 8
- UU500 Unloader, Giant 13 @ 2400 psi
- UU655 Unloader-Modular For Cat 5DX
- UURK7 Repair Kit K7 Unloader
- UURK8 Piston Asm, K7 Unloader



UU320



UU323



UU260



UU325



UU371



UU380

STRAINERS

- D0021 Screen Washer Garden HA
- VF042 Strainer Chemical Brass
- VF043 Tank Filter 1/4
- VF045 Strainer Chemical w/ Check (Brass)
- VF050 Strainer Tube For 5/8 Barb (Float Tank)
- VF055 High Pressure Strainer w/ Disconnect
- VF082 Tank Filter 1/2
- VF085 Filter 1/2 In Line
- VF125 Filter 3/4 Y Type
- VF130 200 Mesh Filter Screen 3/4" Filter
- VF135 Filter Flush Valve
- VF140 Filter Screen 75 Mesh 3/4" Filter
- VF160 Filter 1" Y Type



D0021

The VF085 filter is adequate for pressure feed systems up to 5 gpm. For feeding from a tank use the VF125 Y. Strainer 3/4" for up to 6 gpm. Use VF160 1" strainer for up to 10 gpm.



VF085

Hydro Tek's unique Y-filter can be cleaned by opening the flush valve.

VF135



VF125

PRESSURE RELIEF VALVES

- UP010 Pressure Relief 1500 Brown
- UP045 Pressure Relief 4500 Red
- UP050 Pop Off Valve 5800 psi
- UP060 Pressure Relief 6000 psi
- UP120 Pressure Relief 2000 psi Orange
- UP128 Pressure Relief 2800 psi Blue
- UP137 Pressure Relief 3700 psi Black



UP137

VALVES

- ECH70 Knob, 1.25ID x 1.50D Blue
- ECH72 Knob, 1.25ID x 1.50D Red
- UPT45 Thermal Dump Valve 145F 3/8" MPT
- UPT46 Thermal Dump Valve 145F 1/2" MPT
- VA010 E-Z Start Valve
- VR065 Check Valve 5000 psi 4 gpm Stainless
- VVB08 Ball Valve 1/2"
- VVB38 Ball Valve 3/4" 3 Way
- VVC10 Chem. Met. Valve (Stainless)-Less Knob
- VVC30 Flow Valve 20 gph
- VVF08 Float Valve 3/8 Brass
- VVF15 Float Valve-Robertson Brand

VVF08



VVB38



BURST DISCS

- UPB05 Burst Disc Adapter
- UPB10 Burst Disc 5000-Requires UPB05
- UPB80 Burst Disc 8000-Requires UPB05

FILTRATION

MICRON	200	130	100	80	22	5
MESH	75	120	155	200	450	----

Hydro Man Tip:



Checking your filters daily will help to ensure proper water flow. Filters are located inside the float tank (if equipped) and the screen washer on the garden hose adapter. Always install a filter when running from a supply tank. 5 microns for recycled water, 75 mesh for garden hose, 200 mesh for a hydrant.