

Two Cylinders . . . for the Price of One



Model# SS35003VG – \$5995 list price
14hp (480cc) Vanguard Twin

compare with
SS30003HG – \$5995 list price
270cc (9hp) Honda

Technical Data:

- 3500psi, 3.0gpm
- 12v burner system
- Adjustable temperature up to 250°
- 14hp twin cylinder, key start Vanguard gas engine
- Direct drive General Pump
- Wheel kit or trailer options available

Wheel kit or trailer
options available



Bonus features on SS35003VG:

- 55% more horse power than 270cc (9hp)
- Faster cleaning with higher pressure spray of 3500psi
- Safe refueling: tank not mounted on top of engine to avoid fuel spill fires
- Large 8gal. fuel tank extends run time and eliminates refueling interruption
- Full lubrication, instead of splash lube, with spin-on oil filter cleans oil and protects engine components to ensure maximum lubrication and long life
- Less vibration with two cylinders
- Convenience: Easy starting electric starter

Introductory List Price \$5995

Steam / Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine, 12v Burner

The **SS Series** is a power washer that uses the 12-volt charging system on the engine to power the diesel-fired burner giving you continuous hot water. Its compact size allows passage through standard doorways, and simple design makes it easy to run and maintain. The SS series is versatile, you select a mounting option: on a trailer, on a truck, on wheels or stationary. The SS Series has the output to perform heavy duty cleaning without needing any outside electrical power. Simply turn the key for high pressure, hot cleaning strength. An invaluable piece of equipment for property management companies, farmers, mechanics or anyone requiring a mobile cleaning solution for dirt, grease, and grime.

PRESSURE	3500psi
FLOW CAPACITY	3gpm
OUTLET TEMP	Adjustable thermostat up to 250°F (140°F heat rise)
POWER/ENGINE	14hp Vanguard – electric key start
ENGINE FUEL/CAP	Unleaded, 8 gal
CONTROLS/SWITCHES	Adjustable thermostat, lighted control switch
PUMP	General Pump
POWER DRIVE	Direct Drive
PRESSURE CONTROL	Pressure regulating unloader, safety burst disc, thermal relief valve
WATER SUPPLY	Pressure feed from garden hose (no float tank)
PRESSURE HOSE	3/8" x 50', 4000psi
GUN/WAND	48" molded insulator wand with quick coupler
SOAP INJECTION	Downstream
NOZZLE	Size 4 (0°, 15°) 3.5 (25° Steam) 65 (Soap)
BURNER COIL	1/2" sch. 80 coil, 4 pancake, ceramic blanket insulation
BURNER/POWER	Oil fired, 12V, 20amp circuit breaker, auto ignition, inline fuel filter
BURNER FUEL/CAP	Diesel fuel, kerosene, or fuel oil, 8 gallons
FRAME CONSTRUCTION	Heavy gauge steel, powder coated, Pro-Tec-It frame, Stainless panels and coil wrap
WHEELS	Optional wheel kit available
WEIGHT/DIMENSION	(need) / 45 x 21 x 40

Specifications subject to change without notification and may vary due to ambient conditions



Featuring:

- ✓ **Rugged "Pro-Tec-It" Frame** can be truck or trailer mounted or rolled through a 30" doorway with the optional wheel kit.
- ✓ **Stainless Steel** panels for Lifetime Corrosion Resistance
- ✓ **Commercial / Industrial engines** with high output charging systems

Options...

Hose Reel (AR188), Wheel Kit w/handle and hose hooks (AHA12), 13" w/pull bar steering (AHB12), Mobile Wash Trailer

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

