

Cold (HOT*) Water: Electric Powered – Stationary or Portable

The **CW Series** is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply* (up to 160°F standard or up to 190°F with an optional seal kit). The CW's versatile design allows it to be wall-mounted, floor mounted or portable depending on the cleaning task or application. The auto on/off feature allows you to clean with just one squeeze of the spray gun – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover and, belt driven pump provide a lifetime of continuous performance.

PRESSURE	1200psi
FLOW CAPACITY	2.5gpm
POWER / ENGINE	2.0hp
VOLTS / PHASE / AMPS	115v / 1ph / 17amp
CONTROLS / SWITCHES	Hour meter, lighted on/off switch, 20amp GFCI
PUMP	Cat Pump, oil bath, Triplex, ceramic plunger, brass head, stainless steel valves
POWER DRIVE	V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance
PRESSURE CONTROL	Adjustable pressure unloader, 24v adjustable timer with 7 to 300 second control
WATER SUPPLY	Pressure Feed from Garden Hose
WATER TEMPERATURE	Inlet water temperature from hot water source up to 190°F*
SOAP INJECTION	Downstream soap/chemical injection, activated from the spray wand
PRESSURE HOSE	3/8" x 50' 3000psi Wire Braided Hose
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler
NOZZLE	#4.5 x 0°, 15°, 40°
FRAME CONSTRUCTION	Stainless Steel frame, panels and removable cover
WHEELS	Optional wheel/handle kit available
DIMENSIONS (LxWxH)	28" x 21" x 14" (Dim with wheel kit: 39" x 29 1/2" x 36")
NET WEIGHT	150#

Specifications subject to change without notification and may vary due to ambient conditions.

* accepts water from hot water heater or other hot water source up to 160°F standard or up to 190°F with an optional seal kit

Featuring:

- ✓ **Removable cover** for easy access and serviceability.
- ✓ **Unique integrated wall mount design** frees up valuable floor space
- ✓ **Cat V-belt driven pump** for long lasting performance
- ✓ **Auto ON/Off** with time delay shutdown saves time & effort.

Options...

Hot seal kit (HH3CP), Multi station outlets (ACW20), Wall Mount Brackets Sideways Mount (ACW09), Wall mount hose reels (AR187-3000psi or AR188-5000psi), Wheel/handle kit (AHS15), 24 volt remote start/stop with 50' cord (AEN35)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



CN Series and CW Series both pictured. (CN shown w/optional wheel kit)

