

### Cold (HOT\*) Water: Electric Powered – Stationary or Portable

The **CW Series** is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply\* (up to 160°F standard or up to 190°F with an optional seal kit). The CW's versatile design allows it to be wall-mounted, floor mounted or portable depending on the cleaning task or application. The auto on/off feature allows you to clean with just one squeeze of the spray gun – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover and, belt driven pump provide a lifetime of continuous performance.

<b>PRESSURE</b>	2100psi
<b>FLOW CAPACITY</b>	4.0 gpm
<b>POWER / ENGINE</b>	6.5 hp
<b>VOLTS / PHASE / AMPS</b>	208/230V / 1ph / 28amp
<b>CONTROLS / SWITCHES</b>	Hour meter, lighted on/off switch, 30amp GFCI
<b>PUMP</b>	Cat Pump, oil bath, Triplex, ceramic plunger, brass head, stainless steel valves
<b>POWER DRIVE</b>	V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance
<b>PRESSURE CONTROL</b>	Adjustable pressure unloader, 24v adjustable timer with 7 to 300 second control
<b>WATER SUPPLY</b>	Pressure Feed from Garden Hose
<b>WATER TEMPERATURE</b>	Inlet water temp. from hot water source up to 190°F*
<b>SOAP INJECTION</b>	Downstream soap/chemical injection, activated from the spray wand
<b>PRESSURE HOSE</b>	3/8" x 50' 3000psi Wire Braided Hose
<b>GUN / WAND</b>	48" molded insulator, adj. pressure wand with quick coupler
<b>NOZZLE</b>	#5.5 x 0°, 15°, 40°
<b>FRAME CONSTRUCTION</b>	Stainless Steel frame, panels and removable cover
<b>WHEELS</b>	Optional wheel/handle kit available
<b>DIMENSIONS (LxWxH)</b>	28" x 21" x 14" (Dim with wheel kit: 39" x 29 1/2" x 36")
<b>NET WEIGHT</b>	155#

Specifications subject to change without notification and may vary due to ambient conditions.

\* accepts water from hot water heater or other hot water source up to 160°F standard or up to 190°F with an optional seal kit

#### Featuring:

- ✓ **Removable cover** for easy access and serviceability.
- ✓ **Unique integrated wall mount design** frees up valuable floor space
- ✓ **Cat V-belt driven pump** for long lasting performance
- ✓ **Auto ON/Off** with time delay shutdown saves time & effort.

#### Options...

Hot seal kit (HH3CP), Multi station outlets (ACW20), Wall Mount Brackets Sideways Mount (ACW09), Wall mount hose reels (AR187-3000psi or AR188-5000psi), Wheel/handle kit (AHS15), 24 volt remote start/stop with 50' cord (AEN35)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_



CN Series and CW Series both pictured. (CN shown w/optional wheel kit)