

Steam / Hot / Cold Water Pressure Steamer – Natural Gas or LP Heated, Electric Motor

The **HN Pro Line® Series** is a heavy-duty stationary unit offering high output and instant cleaning power with adjustable temperature for various cleaning applications. The Stainless Steel enclosure offers lifetime corrosion resistance and accessibility to components. High torque / low RPM belt driven pump ensures years of worry free service with built in overheat protection if machine is left on. The automatic electronic ignition eliminates the need to manually light a pilot and increases the safety of the machine.

PRESSURE	3000
FLOW CAPACITY	4.8
OUTLET TEMP	Adjustable to 250°F (130°F Rise)
POWER/ENGINE	10 hp
VOLTS/PHASE/AMPS	E3H is 208v/230v / 3ph / 30amp E4H is 460v / 3ph / 14amp
CONTROLS/SWITCHES	Lighted rocker switches, panel mounted soap control, adjustable thermostat
PUMP	AR Pump, Triplex Ceramic Plunger
POWER DRIVE	V-Belt Drive with Integrated Tension Adjustment
PRES. CONTROL	K-7 Total Relief with <i>By-Pass-Cool</i> System / Safety Relief Valve and Burst Disc
WATER SUPPLY	4 Gallon Float Tank with Double Filtration and Back Flow Prevention
PRESSURE HOSE	3/8 x 50' Steel Wire Braided / 250°F 3000 psi Rated
GUN / WAND	48" molded insulator wand, with quick coupler
SOAP INJECTION	Full Pressure Chemical Injection, Precision Stainless Steel Metering Valve
NOZZLE	#5.5 (0°, 15°, 40°), #4.5 (25° Steam)
BURNER COIL	1/2" x 220' Schedule 80, 7 Pancake, Ceramic Insulation and Stainless Steel Wrap and Cap
BURNER/POWER	Natural Gas with Auto Ignition and 90 Second Safety Lockout, Cast Iron Ring, Brass Jets
BURNER INPUT	440,000 BTU
CONSTRUCTION	Powder coated support base and frame, stainless steel wrap, cover and panels
WHEELS	Wheel kit option available for LP version
WEIGHT/DIM	492#, 47x48x24

*Specifications subject to change without notification and may vary due to ambient conditions.



Featuring:

- ✓ **Adjustable Thermostat** with steam setting for various cleaning applications
- ✓ **By-Pass-Cool** system protects pump from overheating if left on after use
- ✓ **24 Volt Automatic Ignition** system on low emission natural gas burner

Options...

Hose Reel (AR008, AR187, AR188) Draft Diverter (BGD10), Multiple wash station shut-off (ACW20), Wind-up remote timer (AEN80), LP Conversion (BGV05), Wheel Kit for LP version (AHB12), Hour meter kit (EM620)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

