

**HN Series – Natural Gas / LP  
2-gun, adjustable flow****Steam / Hot / Cold Water Pressure Steamer – Natural Gas or LP Heated, Electric Motor**

The **HN Pro Line® Series** is the ideal stationary unit offering high-output for instant cleaning power. The HN30008 is equipped with an adjustable flow feature giving you the option to run two operators at the same time or to reduce the flow of a single user while maintaining pressure. The electronic ignition and optional multiple-user stations make it the perfect machine for industrial in-plant cleaning. The HN is equipped with stainless steel panels for a lifetime of corrosion resistance and an option of liquid propane is also available. This is a great piece of equipment for mining, fleet managers, processing plants and factories everywhere.

<b>PRESSURE</b>	3000 psi
<b>FLOW CAPACITY</b>	7.4 gpm (Two gun at 3.7 each)
<b>OUTLET TEMP</b>	Adjustable up to 200° F
<b>POWER/ENGINE</b>	15 hp industrial motor
<b>VOLTS / PHASE/ AMPS</b>	E3H is 208v/230v / 3ph / 39amp      E4H is 460v / 3ph / 17amp
<b>CONTROLS/SWITCHES</b>	Lighted on/off switches, panel mounted soap control, adjustable thermostat
<b>PUMP</b>	AR Pump, oil bath, Triplex, ceramic plunger, brass head, stainless steel valves
<b>POWER DRIVE</b>	V-Belt Drive
<b>PRESSURE CONTROL</b>	Adjustable Pressure unloader, industrial fittings, safety relief valve, safety burst disc
<b>WATER SUPPLY</b>	4 gallon float tank
<b>PRESSURE HOSE</b>	Qty 2) 3/8" x 50' Steel Wire Braided, 250°F, 3000psi rated
<b>GUN / WAND</b>	Qty 2) 48" molded insulator wand, with quick coupler
<b>SOAP INJECTION</b>	Full pressure Inlet soap/chemical injection, Precision Stainless Steel Metering Valve
<b>NOZZLE</b>	1) qty #8.5 (40°) and 2) qty #4.5 (15°)
<b>BURNER COIL</b>	½" Sch 80 - 8 Pancake Coil with Ceramic Insulation
<b>BURNER/POWER</b>	Natural Gas Cast Iron Ring, Automatic Electronic Ignition
<b>BURNER INPUT</b>	70 Nozzles - 700,000 BTU
<b>FRAME CONSTRUCTION</b>	Powder coated steel frame and base, stainless steel coil wrap, panels and cover
<b>NET WEIGHT/DIMENSION</b>	738#, 54" x 24" x 48"

\*Specifications subject to change without notification and may vary due to ambient conditions.

**Featuring:**

- ✓ **Two man system:** System comes ready for two-man operation, second gun and hose included.
- ✓ **By-Pass-Cool System** protects pump from overheating if left on after use

**Options...**

12" Draft Diverter (BGD12), Hose Reels (AR008) Remote Wash Outlets (ACW20), Remote shut-off timer kit (AEN80), LP Conversion (BGV06), Hour meter kit (EM620)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_

