

HN Series – Natural Gas / LP 2-gun, adjustable flow

Steam / Hot / Cold Water Pressure Steamer – Natural Gas or LP Heated, Electric Motor

The **HN Pro Line® Series** is the ideal stationary unit offering high-output for instant cleaning power. The HN30008 is equipped with an adjustable flow feature giving you the option to run two operators at the same time or to reduce the flow of a single user while maintaining pressure. The electronic ignition and optional multiple-user stations make it the perfect machine for industrial in-plant cleaning. The HN is equipped with stainless steel panels for a lifetime of corrosion resistance and an option of liquid propane is also available. This is a great piece of equipment for mining, fleet managers, processing plants and factories everywhere.

PRESSURE	3000 psi
FLOW CAPACITY	7.4 gpm (Two gun at 3.7 each)
OUTLET TEMP	Adjustable up to 200° F
POWER/ENGINE	15 hp industrial motor
VOLTS / PHASE/ AMPS	E3H is 208v/230v / 3ph / 39amp E4H is 460v / 3ph / 17amp
CONTROLS/SWITCHES	Lighted on/off switches, panel mounted soap control, adjustable thermostat
PUMP	AR Pump, oil bath, Triplex, ceramic plunger, brass head, stainless steel valves
POWER DRIVE	V-Belt Drive
PRESSURE CONTROL	Adjustable Pressure unloader, industrial fittings, safety relief valve, safety burst disc
WATER SUPPLY	4 gallon float tank
PRESSURE HOSE	Qty 2) 3/8" x 50' Steel Wire Braided, 250°F, 3000psi rated
GUN / WAND	Qty 2) 48" molded insulator wand, with quick coupler
SOAP INJECTION	Full pressure Inlet soap/chemical injection, Precision Stainless Steel Metering Valve
NOZZLE	1) qty #8.5 (40°) and 2) qty #4.5 (15°)
BURNER COIL	1/2" Sch 80 - 8 Pancake Coil with Ceramic Insulation
BURNER/POWER	Natural Gas Cast Iron Ring, Automatic Electronic Ignition
BURNER INPUT	70 Nozzles - 700,000 BTU
FRAME CONSTRUCTION	Powder coated steel frame and base, stainless steel coil wrap, panels and cover
NET WEIGHT/DIMENSION	738#, 54" x 24" x 48"

*Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- ✓ **Two man system:** System comes ready for two-man operation, second gun and hose included.
- ✓ **By-Pass-Cool System** protects pump from overheating if left on after use

Options...

12" Draft Diverter (BGD12), Hose Reels (AR008) Remote Wash Outlets (ACW20), Remote shut-off timer kit (AEN80), LP Conversion (BGV06), Hour meter kit (EM620)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

