

Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine

The **SC Series** is a high output hot mobile wash skid with serious cleaning power. It was designed to withstand the daily use by professionals who rely on its dependability to make a living. Its high impact power enables it to handle just about any size cleaning task with ease and without the need for an outside power source. If portability is needed add a wheel kit or mount on a trailer, truck bed or tank skid.

| | |
|--------------------------|--|
| PRESSURE | 3500psi (241 bar) |
| FLOW CAPACITY | 4.5gpm |
| OUTLET TEMP | Adjustable thermostat to 250°F (140°F Rise) |
| POWER/ENGINE | 18hp Vanguard |
| ENGINE FUEL/CAP | Unleaded, 8 gal |
| CONTROLS/SWITCHES | Adjustable thermostat, lighted burner control switch, optional hour meter available |
| PUMP | Cat triplex pump |
| POWER DRIVE | Belt drive, continuous duty performance, easy tension rails |
| PRESSURE CONTROL | K-7 total relief unloader, safety relief valve and burst disc |
| WATER SUPPLY | Pressure feed from garden hose or connect to bulk supply tank (No float tank) |
| PRESSURE HOSE | 3/8" x 50', 4000psi, 250° rated |
| GUN / WAND | 48" molded insulator wand with nozzle holder and quick coupler |
| SOAP INJECTION | Optional soap injection available |
| NOZZLE | #4.5 (15°,40°) #4.0 (25° steam) |
| BURNER COIL | 1/2" sch. 80 coil pipe, 4 pancake, ceramic blanket insulation, double wall stainless enclosure |
| BURNER/POWER | Oil fired, 115v, Auto Ignition, Forced Draft, Fuel Filter, Fuel Solenoid |
| BURNER FUEL/CAP | Diesel Fuel #1 or #2, Kerosene, or fuel oil – 18 Gallons |
| GENERATOR | On-board 2900 watt, 115v generator for auxiliary power |
| CONSTRUCTION | Rugged, powder coated Pro-Tect-It frame, rustproof stainless panels and coil wrap |
| WHEELS | Optional wheel kit available |
| WEIGHT/DIM. | 588#, 51"x34"x41" |

Specifications subject to change without notification and may vary due to ambient conditions



Featuring:

- ✓ **On-board Generator** provides supplemental power outlets to run lights or other accessories
- ✓ **Super Duty Heating system** uses schedule 80 coil, double wall stainless steel, and ceramic insulation combined with a proven 115v oil fired burner for durability and efficiency
- ✓ **Commercial/Industrial Engines** Twin cylinder, overhead valve for reduced emissions and maintenance. Full pressure lubrication and oil filter for long life.

Options...

Hose Reel (AR188 or AR186), Stainless frame option (HS215), Wheel Kit 13" w/pull bar steering (AHB12), locking kit for wheels (AHB20), Trailer, Tank Skid, Down Stream Injection (AC340), Float Tank w/inlet injection (WT0SD), Winterizing Tank (WT0SC), Hour Meter (AM601), Hydro Vacuum wastewater recycle

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

