

## SCU Series – Mobile Wash Skid 2 Gun, adjustable flow

### Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine

Experience ultimate duty cleaning power. The **SCU Series 2-gun** system has unbeatable water flow output and heat rise with 614,000 BTU's to get the job done much faster than comparable hot washers. The SCU Series has a rust proof, stainless steel frame and long lasting, quality components to withstand the daily use that a professional demands. The built-in generator has additional capacity to run lights or water recycle accessories and you can also carry water with the optional ProTowWash trailer for total self-containment.

<b>PRESSURE</b>	3500psi
<b>FLOW CAPACITY</b>	8.7gpm (two operators 4.3gpm ea.)
<b>OUTLET TEMP</b>	Panel Mounted Adjustable Thermostat to 200°F, 100°F Rise
<b>POWER/ENGINE</b>	31hp Vanguard, key start
<b>ENGINE FUEL/CAP</b>	Unleaded Gasoline, 18 gallons for extended runtime
<b>CONTROLS/SWITCHES</b>	Lighted On/Off switch, hour meter, adjustable temperature, soap control, aux. power, pressure gauge
<b>PUMP</b>	General Pump, oil bath, triplex ceramic plunger, brass head, stainless steel valves
<b>POWER DRIVE</b>	V-belt, low RPM-cooler, quieter, continuous duty performance. Easy Tension Rails
<b>PRESSURE CONTROL</b>	Adjustable pressure unloader, safety burst disc, flow switch, pressure switch, gauge
<b>WATER SUPPLY</b>	Minimum 25 gallon bulk supply tank required
<b>PRESSURE HOSE</b>	Qty 2) 3/8" x 50' double steel wire braid, 250°F rated, 5800psi hose
<b>GUN / WAND</b>	Qty 2) 48" molded insulator wand with multi-nozzle holder and quick coupler
<b>NOZZLE</b>	Qty 2) #4.5 (0°, 15°, 40°)
<b>SOAP INJECTION</b>	Full pressure inlet soap injection
<b>BURNER COIL</b>	1/2" sch 80 steel coil, 4 pancake, ceramic blanket insulation
<b>BURNER/POWER</b>	Wayne Oil Fired, 115v, Automatic Ignition, Fuel Filter w/Water Separator, Fuel Solenoid
<b>BURNER FUEL/CAP</b>	Diesel Fuel #1 or #2, Kerosene, 18 Gal. capacity for extended run time up to 8 hours
<b>GENERATOR</b>	On-board 2900 Watt, 115v generator for auxiliary power
<b>CONSTRUCTION</b>	Stainless 1 1/4" tube frame, 14 gauge base, stainless panels and coil wrap
<b>WHEELS</b>	Optional wheel kit available
<b>WEIGHT/DIM</b>	674#, 48" X 38" X 41"

Specifications subject to change without notification & may vary due to ambient conditions – Battery not included.

#### Featuring...

- ✓ **Balanced unloader system** allows two operators to wash at the same time at full pressure.
- ✓ **Ultimate Duty:** More cleaning unit output than any other washer in standard production
- ✓ **Long run time** with 18 gal gasoline and diesel tanks to reduce down time
- ✓ **Rust Proof Construction** – stainless steel lifetime guarantee

#### Options...

Wheel kit 13" w/ pull bar steering (AHB12), locking kit for wheel kit (AHB20), Downstream injection kit (AC360), Antifreeze tank/valve-installed (AW008), Trailer, Tank Skid, Hydro Vacuum wastewater recovery

TO: \_\_\_\_\_  
 COMMENTS: \_\_\_\_\_  
 YOUR PRICE: \_\_\_\_\_  
 DISTRIBUTED BY: \_\_\_\_\_



ETL Listed  
 Certified to UL 1776  
 Certified to  
 CAN/CSA B140.11

