

**ProTowWash® – Transport Trailer with 185 Gallon Tank**

The T200 single axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The 185 Gallon water tank provides ample water to sustain many remote-cleaning requirements. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum. Long life, rugged, durable and dependable service are engineered into the T200 Series Pro Tow Wash.

TECHNICAL DATA	T200N	T200E
MACHINE CAPACITY	SS, SC, SCU Series	
SUSPENSION / AXLE	Single 3700# Torsion Axle-Up to 300% more wheel travel over conventional trailer	
TRAILER BRAKES	None	Electric Brake, Breakaway Switch***
WHEEL / TIRE	2 - 14" White Spoke Rim, 5 Lug / ST205/75D 14 Tires, 1760 Pounds capacity per tire	
COUPLER / TONGUE	2" Ball Coupler, Dual Safety Chains	
VEHICLE HITCH/GVWR	2" Ball Hitch, Class III 5000 Pound Rated, 21" to top of ball when trailer is attached 3500# GVWR	
FENDERS	12 GA Steel Fender with recessed Tail light mounting	
LIGHTS	Recessed Rubber Grommet Snap-In, 4 Pole Flat Wiring Connector, DOT Approved	
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter	
WATER TANK	185 Gallon Capacity, Seamless Polyethylene, 10" lid, Garden Hose Fill Fitting	
TANK DRAW/FILTER	1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve	
FRAME CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish	
WEIGHT / DIMENSIONS	496 Lbs. Empty (No Machine) 125" x 70" x 61"	

\*Specifications subject to change without notification and may vary due to ambient conditions.

Note: Shipped To Distributors Only – Not Available to Drop Ship – Assembly Required

\*\*\* Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery.

**Featuring:**

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Stainless Exhaust Pipe Extension:** Lifetime corrosion resistance insures no need to replace in a few years.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination

**Options...**

Hose Reels, Lunette eye hitch, Stainless advertising panels, Chrome wheel upgrade, Front Bucket Rack (ACR02), 3-way ball valve (AW006), Light Bar rack (HLB98), Pump seal saver bypass (APS50)-installed, Low water shutdown (AW410)-installed, Sand hopper, Hydro Vacuum wastewater recycle, 12v Chemical sprayer with 40g tank (AC440)



Pressure washer not included  
 Shown with optional Hose Reel and Light Bar

**TO:** \_\_\_\_\_

**COMMENTS:** \_\_\_\_\_

**YOUR PRICE:** \_\_\_\_\_

**DISTRIBUTED BY:** \_\_\_\_\_

\* **WARNING:** Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.