

ProTowWash® – Transport Trailer with 185 Gallon Tank

The T200 single axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The 185 Gallon water tank provides ample water to sustain many remote-cleaning requirements. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum. Long life, rugged, durable and dependable service are engineered into the T200 Series Pro Tow Wash.

TECHNICAL DATA	T200N	T200E
MACHINE CAPACITY	SS, SC, SCU Series	
SUSPENSION / AXLE	Single 3700# Torsion Axle-Up to 300% more wheel travel over conventional trailer	
TRAILER BRAKES	None	Electric Brake, Breakaway Switch***
WHEEL / TIRE	2 - 14" White Spoke Rim, 5 Lug / ST205/75D 14 Tires, 1760 Pounds capacity per tire	
COUPLER / TONGUE	2" Ball Coupler, Dual Safety Chains	
VEHICLE HITCH/GVWR	2" Ball Hitch, Class III 5000 Pound Rated, 21" to top of ball when trailer is attached 3500# GVWR	
FENDERS	12 GA Steel Fender with recessed Tail light mounting	
LIGHTS	Recessed Rubber Grommet Snap-In, 4 Pole Flat Wiring Connector, DOT Approved	
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter	
WATER TANK	185 Gallon Capacity, Seamless Polyethylene, 10" lid, Garden Hose Fill Fitting	
TANK DRAW/FILTER	1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve	
FRAME CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish	
WEIGHT / DIMENSIONS	496 Lbs. Empty (No Machine) 125" x 70" x 61"	

*Specifications subject to change without notification and may vary due to ambient conditions.

Note: Shipped To Distributors Only – Not Available to Drop Ship – Assembly Required

*** Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery.

Featuring:

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Stainless Exhaust Pipe Extension:** Lifetime corrosion resistance insures no need to replace in a few years.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination

Options...

Hose Reels, Lunette eye hitch, Stainless advertising panels, Chrome wheel upgrade, Front Bucket Rack (ACR02), 3-way ball valve (AW006), Light Bar (HLB98), Pump seal saver bypass (APS50)-installed, Low water shutdown (AW410)-installed, Sand hopper, Hydro Vacuum wastewater recycle, 12v Chemical sprayer with 40g tank (AC440), Locking storage lid option (ATH50)



Pressure washer not included
 Shown with optional Hose Reel and Light Bar

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

* **WARNING:** Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.