

MOBILE WASH SKID: SELF CONTAINED, DIESEL FIRED, GASOLINE OR DIESEL POWERED

The **SC Pro Line® Series** is a high output hot mobile wash skid with serious cleaning power. It was designed to withstand the daily use by professionals who rely on its dependability to make a living. Its high impact power, rugged stainless steel construction and Pro-Tect-it frame enable it to handle just about any size cleaning task with ease and without the need for an outside power source. SC30005DH has two-cylinder water-cooled diesel engine.

TECHNICAL DATA	SC30005VH	SC30005DH	SC35006VG	SC35006KG
PRESSURE	3000psi (207bar)	3000psi (207 bar)	3500psi (241 bar)	3500psi (241 bar)
FLOW CAPACITY	5.0gpm	5.0gpm	5.5gpm	5.5gpm
OUTLET TEMP	Panel mounted adjustable thermostat to 200°F (140°F Rise)			
ENGINE	16hp Vanguard V-Twin	13.3hp Kubota	21hp Vanguard	20hp Kohler
FUEL/CAPACITY	Unleaded, 7.5gal	Diesel, 15 gal	Unleaded, 7.5gal, 8hrs run time	
PUMP	AR triplex pump		General triplex pump	
PRESSURE CONTROL	K-7 total relief unloader, safety relief valve and burst disc			
WATER SUPPLY	Pressure feed from garden hose or connect to bulk supply tank (No float tank)			
POWER DRIVE	Belt drive, low RPM: cooler, quieter, continuous duty performance, easy tension rails			
PRESSURE HOSE	3/8" x 50', 3000psi, 250° rated		3/8" x 50', 4000psi, 250° rated	
GUN / WAND	Insulated Shut Off Gun, 48" Insulated Wand with Nozzle Quick Coupler			
NOZZLE	#5.5 (0°,15°,40°)			#6.0 (0°,15°,40°)
BURNER COIL	½" sch. 80 coil pipe, 4 pancake, ceramic blanket insulation, double wall stainless enclosure			
BURNER	Wayne oil fired, 115v, Auto Ignition, Forced Draft, Fuel Filter, Fuel Solenoid			
BURNER FUEL	Diesel Fuel #1or#2, Kerosene, 18 Gal. Capacity (8 hours run time)			
BURNER POWER	2900 watt 115v generator, aux. GFCI power outlet, diagnostic lights, 15a breaker			
WEIGHT/DIM.	605#, 51"x34"x41"	721#, 51"x34"x39"	632#, 51"x34"x41"	646#, 51"x34"x41"

*Specifications subject to change without notification and may vary due to ambient conditions



Featuring:

- ✓ **Rugged "Pro-TECT-It" Frame** can be truck or trailer mounted or hoisted utilizing the built-in lifting eyes (Stainless frame on SC30005DH)
- ✓ **Total Relief Unloader** improves operator control and safety while enhancing reliability by eliminating trapped pressure and hard engine starting.
- ✓ **Commercial/Industrial Engines** Twin cylinder, overhead valve for reduced emissions and maintenance. Full pressure lubrication and oil filter for long life.
- ✓ **Super Duty Heater** uses schedule 80 coil pipe and double wall stainless steel and ceramic insulation combined with a proven 115 volt oil fired burner for durability
- ✓ **Onboard Generator** provides supplemental power outlets to run lights or accessories.

Options...

Hose Reel (AR188), Down Stream Injection, Battery (EB24F), Racor Fuel Filter, Wheel Kit 13" (AHB12), locking kit for wheel kit (AHB20), Trailer, Tank Skid, Float Tank w/inlet injection (WT0SS), Lower front panel (HS023), Hour Meter (AM601), Hydro Loop



TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____