

HYDROTEK.US

2353 Almond Avenue Redlands, CA 92374
 Ph 800.274.9376 Fax 909.799.9888
 www.hydrotek.us



HOT/COLD/STEAM MOBILE WASH SKID: DIESEL FIRED, GAS POWERED

Experience ultimate duty cleaning power. The **SCU Series** has the reserve horsepower and heat rise to get the job done faster, with less soap and reduced noise pollution. It has a rust proof, stainless steel frame and long lasting, quality components to withstand the daily use that a professional demands. The built-in generator has additional capacity to run lights or water recycle accessories and you can also carry water with the optional ProTowWash trailer for total self-containment.

TECHNICAL DATA	SCU33005V	SCU35005KQ*	SCU35006VQ*	SCU35006HQ*
PRESSURE	3300psi	3500psi	3500psi	3500psi
FLOW CAPACITY	4.5gpm	4.6gpm	5.6gpm	5.6gpm
OUTLET TEMP	Panel mounted adjustable temperature to 250°F (140° + rise)			
POWER/ENGINE	16hp Vanguard	20hp Kohler	21hp Vanguard	24hp Honda
ENGINE FUEL/CAP	Unleaded gasoline, 18 gallons for extended runtime, up to 2 days			
CONTROLS/SWITCHES	Lighted on/off switches, hour meter, adj. thermostat, soap control, aux. power			
PUMP	Cat Pump		General Pump	
POWER DRIVE	V-belt, low RPM-cooler, quieter, continuous duty performance. Easy Tension Rails			
PRESS. CONTROL	Total relief unloader, 0-5000psi gauge, safety burst disc, relief valve, pressure switch			
WATER SUPPLY	4 Gal. float tank, double inlet filtration, 3 way inlet valve			
PRESSURE HOSE	3/8" x 50' double steel wire braid hose 250°F 5000psi rated			
GUN/WAND	48" molded insulator wand with multi-nozzle holder and quick coupler			
SOAP INJECTION	Full pressure inlet injection, stainless precision metering valve			
NOZZLE	#5(0°,15°,40°,Steam)	#4.5(0°,15°,40°,Steam)	#5.5(0°,15°,40°,Steam)	
BURNER COIL	1/2" sch 80 steel coil, 4 pancake, ceramic blanket insulation, double wall stainless enclosure			
BURNER/POWER	Oil Fired, 115v, Automatic Ignition, Fuel Filter w/Water Separator, Fuel Solenoid			
BURNER FUEL/CAP	Diesel Fuel #1 or #2, Kerosene, or fuel oil, 18 gallons			
GENERATOR	On-board 2900 watt, 115v generator for auxiliary power			
CONSTRUCTION	Stainless 1 1/4" tube frame, 14 gauge base, stainless panels and coil wrap			
WHEELS	Optional wheel kit available			
WEIGHT/DIMENSION	(need weight) 48"x38"x41"			

Specifications subject to change without notification & may vary due to ambient conditions – battery not included

*Q=Quiet Models <80db @25'

Featuring...

- ✓ **Safe to use** flow sensitive unloader builds up pressure gradually to reduce gun recoil and relieve trapped pressure
- ✓ **More Standard Controls** incl. 3-way inlet valve, hour meter, pressure gauge, soap injection, lighted on/off switches, auxiliary power switch, and thermostat with steam.
- ✓ **Rust Proof Construction**-Stainless steel lifetime guarantee

Options...

Hose Reel (AR188), Wheel Kit 13" w/ pull bar steering (AHB12), locking kit for wheel kit (AHB20), Downstream injection kit (AC340), Trailer, Tank Skid, Hydro Loop wastewater recycle

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



SCU35009VAF shown