

### HOT/COLD PRESSURE STEAMER: NATURAL GAS/LP FIRED, ELECTRIC POWERED

The **HN Pro Line® Series** is the ideal stationary unit offering 2-gun high-output for instant cleaning power. The electronic ignition and optional multiple-user stations make it the perfect machine for industrial in-plant cleaning. The HN is equipped with stainless steel panels for a lifetime of corrosion resistance and an option of liquid propane is also available. This is a great piece of equipment for mining, fleet managers, processing plants and factories everywhere.

TECHNICAL DATA	HN30008E3H	HN30008E4H	HN30008E8H
PRESSURE	3000 psi		
FLOW CAPACITY	7.4 gpm (Two gun at 3.7 each)		
OUTLET TEMP	Adjustable up to 200° F		
POWER/ENGINE	15 hp industrial motor		
VOLTS / PHASE/ AMPS	230V / 3PH / 34	460V / 3PH / 17	208V / 3PH / 38
CONTROLS/SWITCHES	Lighted on/off switches, panel mounted soap control, adjustable thermostat		
PUMP	AR Pump, oil bath, Triplex, ceramic plunger, brass head, stainless steel valves		
POWER DRIVE	V-Belt Drive		
PRESSURE CONTROL	Adjustable Pressure unloader, industrial fittings, safety relief valve, safety burst disc		
WATER SUPPLY	4 gallon float tank		
PRESSURE HOSE	Qty 2) 3/8" x 50' Steel Wire Braided, 250°F, 4000psi rated		
GUN / WAND	Qty 2) 48" molded insulator wand, with quick coupler		
SOAP INJECTION	Full pressure Inlet soap/chemical injection, Precision Stainless Steel Metering Valve		
NOZZLE	1) qty #8.5 (40°) and 2) qty #4.5 (15°)		
BURNER COIL	1/2" Sch 80 - 8 Pancake Coil with Ceramic Insulation		
BURNER/POWER	Natural Gas Cast Iron Ring, Automatic Electronic Ignition		
BURNER INPUT	70 Nozzles - 700,000 BTU		
FRAME CONSTRUCTION	Powder coated steel frame and base, stainless steel coil wrap, panels and cover		
NET WEIGHT/DIMENSION	738#, 54" x 24" x 48"		

\*Specifications subject to change without notification and may vary due to ambient conditions.

#### Featuring:

- ✓ **Standard 2 gun:** System comes ready for two-man operation, second gun and hose included.
- ✓ **By-Pass-Cool System** protects pump from overheating if left on after use

#### Options...

12" Draft Diverter (BGD12), Hose Reels (AR008) Remote Wash Outlets (ACW20), Remote shut-off timer kit (AEN80), LP Conversion (BGV06)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_

