

### HOT/COLD/STEAM PRESSURE STEAMER: NATURAL GAS/LP FIRED, ELECTRIC POWERED

The **HN Series** is an ideal stationary unit offering high output that is fully controlled at the wash site with its standard remote control. It delivers the ultimate in convenience to save time and money: no fuel tanks to fill, no pilot to light, no garden hose to hunt down, no running back to the machine to turn the soap on, it even has automatic shut off. This rugged and proven washer will perform and thrive under the harshest industrial applications. Its versatile cleaning power is preferred by mining, fleet managers, processing plants, and factories everywhere.

| TECHNICAL DATA           | HN20004E8R   | HN21004E3R /E4R                    | HN22005E2R       | HN32004E2R       | HN35005E3R /E4R /E8R                                  |
|--------------------------|--|------------------------------------|------------------|------------------|---|
| <b>PRESSURE</b>          | 2000   | 2100                               | 2200             | 3200             | 3500  |
| <b>FLOW CAPACITY</b>     | 3.8  | 4                                  | 4.3              | 3.5              | 4.3   |
| <b>OUTLET TEMP</b>       | Adjustable up to 250°F, 140°F Rise   |                                    |                  |                  |   |
| <b>POWER/ENGINE</b>      | 5hp  | 6hp                                | 6.5hp            | 7.5hp            | 10hp  |
| <b>VOLTS/PHASE/AMPS</b>  | E8=208v 1ph 22a  | E3=230v 3ph 20a<br>E4=460v 3ph 10a | 230v 1ph 25a     | 230v 1ph 32a     | E3=230v 3ph 27a<br>E4=460v 3ph 14a<br>E8=208v 3ph 30a |
| <b>CONTROLS/SWITCHES</b> | Lighted on/off switches, hour meter, adjustable temperature, panel mounted soap control, hour meter, adjustable auto off timer, Wall-mount remote included |                                    |                  |                  |   |
| <b>PUMP</b>              | Cat Pump, Belt Drive, Triplex Ceramic Plunger  |                                    |                  |                  |   |
| <b>PRESSURE CONTROL</b>  | Total relief K7 unloader, burst disc, safety relief valve, adjustable pressure wand  |                                    |                  |                  |   |
| <b>WATER SUPPLY</b>      | 4 gallon float tank, double inlet filtration, back flow prevention   |                                    |                  |                  |   |
| <b>PRESSURE HOSE</b>     | 3/8 x 50' 5000 psi 250°F Rated and 3/8 x 9' jumper hose for remote   |                                    |                  |                  |   |
| <b>GUN / WAND</b>        | 48" molded insulator, adj. pressure wand, with multi-nozzle holder and quick coupler   |                                    |                  |                  |   |
| <b>SOAP INJECTION</b>    | Full Pressure Inlet soap/chemical injection - Stainless Metering Valve - Soap Solenoid   |                                    |                  |                  |   |
| <b>NOZZLE</b>            | #5.5   | #5.5                               | #5.5             | #4.0             | #4.5  |
|                          | 0°, 15°, 40°, Steam  |                                    |                  |                  |   |
| <b>BURNER COIL</b>       | 1/2" 220' sch. 80, 7 Pancake coil with ceramic insulation and Stainless enclosure  |                                    |                  |                  |   |
| <b>BURNER/POWER</b>      | Natural Gas Cast Iron Ring - Automatic Electronic Ignition   |                                    |                  |                  |   |
| <b>BURNER INPUT</b>      | 360,000 BTU  | 360,000 BTU                        | 440,000 BTU      | 360,000 BTU      | 440,000 BTU   |
| <b>CONSTRUCTION</b>      | All Stainless Steel: frame, panels, coil wrap, legs  |                                    |                  |                  |   |
| <b>WHEELS</b>            | Wheel kit option available for Liquid Propane version  |                                    |                  |                  |   |
| <b>WEIGHT/DIM.</b>       | 531#<br>47x24x48   | 546#<br>47x24x48                   | 539#<br>47x24x48 | 565#<br>47x24x48 | 598#<br>47x24x48                                      |

\*Specifications subject to change without notification and may vary due to ambient conditions.

#### Featuring:

- ✓ **24V remote control** with 100' cable gives operator dual control of all six functions, both at the machine and wash site:  
 1) Pump 2) Detergent 3) Burner 4) Pressure 5) Nozzle selection 6) Hose storage
- ✓ **Super heavy-duty** components and corrosion resistant stainless construction ensure years of trouble free service

#### Options...

Hose Reels (AR008, AR187, AR188) Draft Diverter (BGD10), Extra Remote (AEN60), Liquid Propane Conversion (BGV05), Wheel Kit for LP version (AHB12)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_

