

HOT/COLD/STEAM PRESSURE STEAMER: DIESEL FIRED, ELECTRIC POWERED

The **HX Series** combines the cleaning power of high pressure with the grease cutting effectiveness of hot water. The front mounted controls let you easily adjust the soap ratio and the temperature up to 250°F. The stainless steel panels and advanced features give years of trouble free service. A great piece of cleaning equipment anywhere electrical power is available and fast cleaning is needed.

TECHNICAL DATA	HX21004E2/E3/E4	HX32004E2	HX35005E3/E4
PRESSURE	2100	3200	3500
FLOW CAPACITY	4.0	3.5	4.3
OUTLET TEMP	Adjustable Temperature up to 250° F (170° rise)		
POWER/ENGINE	E2=6.5hp,E3/E4= 6.0hp	7.5hp	10.0hp
VOLTS/PHASE/AMP	E2=230v/1ph/27 E3=230v/3ph/21 E4=460v/3ph/11	230v / 1ph / 34	E3=208/230v/3ph/29 E4=460v/3ph/15
CONTROLS/SWITCHES	Hour meter, lighted on/off switches, adjustable temperature, panel mounted soap control		
PUMP	Cat Pump - Oil Bath, Triplex, Ceramic Plungers, Brass head, Stainless Steel Valves		
POWER DRIVE	Belt Drive		
PRESSURE CONTROL	Regulator controlled, adjustable pressure wand, safety relief valve, safety burst disc		
WATER SUPPLY	4 gallon float tank, double inlet filtration, back flow prevention		
PRESSURE HOSE	3/8" x 50' 250°F 3000psi	3/8" x 50' 250°F 5000psi rated	
GUN / WAND	48" molded insulator, adj. pressure wand with multi-nozzle holder and quick coupler		
SOAP INJECTION	Inlet Chemical Injection at Full Pressure, Stainless Steel Chemical Metering Valve		
NOZZLE	#5.5; 0°, 15°, 40°	#4.0; 0°, 15°, 40°	#4.5; 0°, 15°, 40°
BURNER COIL	1/2" Schedule 80 4 Pancake High Efficiency Coil, Stainless Steel Enclosure		
BURNER/POWER	Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator		
FRAME CONSTRUCTION	Stainless steel frame, coil wrap and panels		
WHEELS	4) 13" tires installed		
NET WEIGHT/DIM.	E2 & E3: 424# E4: 434# 47"x29"x42"	524# 47"x29"x42"	E3: 504# E4: 514# 47"x29"x42"

*Specifications subject to change without notification and may vary due to ambient conditions

Featuring:

- ✓ **Instant Trigger Start (ITS):** The machine and burner starts and stops instantly when the trigger gun is pulled or released.
- ✓ **High Burner Output:** Provides the highest rise in water temperature in its class, even from the coldest water supply, with over 500,000 BTU.
- ✓ **Adjustable Controls for Multiple Applications:** The temperature and soap can easily be adjusted from the front mounted control knobs and the pressure is adjusted at the wand.
- ✓ **Steam Selection at Full Output:** Adjustable knob lets you select steam up to 250° F without the loss of flow, pressure or switching valves or nozzles.

Options...

Hose Reel, 3000psi (AR187), or 5000psi (AR188)



TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____