

MOBILE WASH SKID: SELF CONTAINED, DIESEL FIRED, GASOLINE or DIESEL POWERED

The **SC Series – 2 Gun** offers the most versatile hot water pressure washers on the market today. Each skid comes equipped to allow the operator to vary the flow of the machine and reliably handle a two-gun set-up. The system is engineered to uniquely balance 1 or 2 gun operations. This series is powered by industrial engines, hi torque–low RPM belt driven pumps and a burner system with a 2.9Kw generator, providing clean, reliable 115V power for sustained burner operation. Simply add the second gun/hose kit (part# AVG53) if needed for second operator.

TECHNICAL DATA	SC40006KAF	SC40006VAF	SC40006DAF
PRESSURE	4000psi	4000psi	4000psi
FLOW CAPACITY	5.5gpm	5.5gpm	5.2gpm
OUTLET TEMP	Adjustable to 200°F (120°F rise)		
POWER/ENGINE	20hp Kohler	21hp Vanguard	17hp Kubota
ENGINE FUEL/CAP	Gasoline, 7½ Gal.- 7 hrs		#2 Diesel, 15 gal
CONTROLS/SWITCHES	Adjustable thermostat, lighted burner control switch, (hour meter incl. on SC40006DAF)		
PUMP	AR Pump, Oil Bath, Triplex, Ceramic Plunger pump		
POWER DRIVE	V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails		
PRES. CONTROL	Adjustable Pressure Unloader, High Pressure Industrial Fittings, Safety Burst Disc		
WATER SUPPLY	Minimum 25 gallon bulk supply tank required		
PRESSURE HOSE	3/8" x 50', 4000psi 250° rated		
GUN / WAND	48" molded insulator wand with quick coupler (second gun/hose kit available)		
SOAP INJECTION	Optional downstream soap injection available		
NOZZLE	#5.5, #5, #4 & #2.7 (15°)		
BURNER COIL	½" x 120' sch 80 steel coil, 4 pancake, ceramic insulation, stainless enclosure		
BURNER/POWER	Oil Fired, 115 volt, Auto Ignition, Racor Fuel Filter		
BURNER FUEL/CAP	Diesel #1 or #2, Kerosene, 18 gal. – 6-10 hours of run time		
GENERATOR	On-board 2900 watt, 115v generator for auxiliary power		
CONSTRUCTION	Rugged, powder coated Pro-Tect-It frame with lifting eyes, stainless panels & coil wrap		
WHEELS	Optional wheel kit available		
NET WEIGHT/DIM.	649# 51"x34"x39"	649# 51"x34"x39"	649# 51"x34"x39"

*Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- ✓ **Rugged "Protect-It" Frame** can be truck or trailer mounted or pulled/towed with the optional wheel kit, incl. front panel extension
- ✓ **Super Duty Burner System** uses schedule 80 coil pipe and double wall stainless steel and ceramic insulation combined with a proven 115 volt oil fired burner for trouble free heating
- ✓ **Adjustable Flow System** can be used for 2-gun operation or to conserve water

Options...

Second gun/hose for SC40006 (AVG53), Stainless frame option (HS215), Trailer, Tank Skid, Wheel Kit 13" w/pull bar steering (AHB12), locking kit for wheel kit (AHB20), Wheel kit for SC40006DAF (SC020), Hose Reel (AR186 or AR188), Down stream injection (AC340), Hour meter (AM601), Hydro Loop wastewater recycle

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____





2 GUN - SKID

The SC30008KAF comes standard with second gun and hose

TECHNICAL DATA	SC30008KAF
PRESSURE	3000psi
FLOW CAPACITY	8 gpm (two operators, 4gpm ea.)
OUTLET TEMP	Adjustable to 200°F (120°F rise)
POWER/ENGINE	25hp Kohler
ENGINE FUEL/CAP	Gasoline, 7 ½ Gal. - 6 hrs run time
CONTROLS/SWITCHES	Adjustable thermostat, lighted burner control switch, optional hour meter available
PUMP	AR Pump, Oil Bath, Triplex, Ceramic Plunger pump
POWER DRIVE	V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails
PRES. CONTROL	Adjustable Pressure Unloader, High Pressure Industrial Fittings, Safety Burst Disc
WATER SUPPLY	Minimum 25 gallon bulk supply tank required
PRESSURE HOSE	Qty 2 - 3/8"x50', 4000psi 250° rated
GUN / WAND	Qty 2 – 48" molded insulator wand with quick coupler
SOAP INJECTION	Optional downstream soap injection available
NOZZLE	#8, #7, #6 & #4.5 (15°)
BURNER COIL	½" x 120' sch 80 steel coil, 4 pancake, ceramic insulation, stainless enclosure
BURNER/POWER	Oil Fired, 115 volt, Auto Ignition, Racor Fuel Filter
BURNER FUEL/CAP	Diesel #1 or #2, Kerosene, 18 gal. Capacity, 6-10 hours of run time
GENERATOR	On-board 2900 watt, 115v generator for auxiliary power
CONSTRUCTION	Rugged, powder coated Pro-Tect-It frame with lifting eyes, stainless panels & coil wrap
WHEELS	Optional wheel kit available
NET WEIGHT/DIM.	668# 51"x34"x39"

*Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- ✓ **Rugged "Protect-It" Frame** can be truck or trailer mounted or pulled/towed with the optional wheel kit
- ✓ **Super Duty Burner System** uses schedule 80 coil pipe and double wall stainless steel and ceramic insulation combined with a proven 115v oil fired burner for trouble free heating.
- ✓ **Adjustable Flow System** can be used for 2-gun operation or to conserve water

Options...

Stainless frame option (HS215), Trailer, Tank Skid, Wheel Kit 13" w/pull bar steering (AHB12), locking kit for wheel kit (AHB20), Hose Reels (AR188 or AR186), Down stream injection (AC340), Hour meter (AM601), Lower front panel (HS023), Hydro Loop water recycle

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



Shown with optional stainless panel extension