

## HOT/COLD/STEAM PRESSURE STEAMER: DIESEL FIRED, ELECTRIC POWERED

The **HX Series** combines the cleaning power of high pressure with the grease cutting effectiveness of hot water. It incorporates a high output diesel fired burner with an exceptional heat rise at over 500,000 BTU's. The front mounted controls let you easily adjust the soap ratio and the temperature up to 250°F. The HX series includes trigger start; simply pull the trigger on the spray gun, and instantly the machine turns itself on and delivers hot cleaning power. Release the trigger and the unit shuts off automatically. The stainless steel panels and advanced features give years of trouble free service. A great piece of cleaning equipment anywhere electrical power is available and fast cleaning is needed.

TECHNICAL DATA	HX21004E2/E3/E4	HX32004E2	HX35005E3/E4
PRESSURE	2100	3200	3500
FLOW CAPACITY	4.0	3.6	4.3
OUTLET TEMP	Adjustable Temperature up to 250° F (170° rise)		
ELECTRIC MOTOR	E2=6.5hp,E3/E4= 6.0hp	7.5hp	10.0hp
VOLTS	E2=230v1ph E3=230v3ph E4=460v3ph	230v 1ph	E3=230v3ph E4=460v3ph
AMPERES	E2=24; E3=19; E4=9.5	32	E3=28; E4=14
PUMP	CAT – Belt Driven, Oil Bath, Triplex, Ceramic Plungers, Brass head, Stainless Steel Valves		
CHEMICAL INJECTION	Inlet Chemical Injection at Full Pressure, Stainless Steel Chemical Metering Valve		
PRESSURE CONTROL	Regulator controlled, safety relief valve, safety burst disc		
PRESSURE HOSE	3/8" x 50' 250°F 3000psi	3/8" x 50' 250°F 5000psi rated	
GUN / WAND	Stainless Steel <i>Ultra Gun</i> , Adjustable Pressure Wand		
NOZZLE	#5.5; 0°, 15°, 40°	#4.0; 0°, 15°, 40°	#4.5; 0°, 15°, 40°
BURNER COIL	1/2" Schedule 80 4 Pancake High Efficiency Coil, Stainless Steel Enclosure		
BURNER	Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator		
NET WEIGHT/DIM.	E2 & E3: 424# E4:434# 47"x29"x42"	524# 47"x29"x42"	E3:504# E4:514# 47"x29"x42"

\*Specifications subject to change without notification and may vary due to ambient conditions



### Featuring:

- ✓ **Instant Trigger Start (ITS):** The machine and burner starts and stops instantly when the trigger gun is pulled or released.
- ✓ **High Burner Output:** Provides the highest rise in water temperature in its class, even from the coldest water supply, with over 500,000 BTU.
- ✓ **Adjustable Controls for Multiple Applications:** The temperature and soap can easily be adjusted from the front mounted control knobs and the pressure is adjusted at the wand.
- ✓ **Steam Selection at Full Output:** Adjustable knob lets you select steam up to 250° F without the loss of flow, pressure or switching valves or nozzles.

### Options...

Extension Hose, Wheel Kits (AHS10, AHS12, AHA12), Hose Reel (AR188)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_



Shown with optional wheel kit